
Top All-in-One Solar Street Light Manufacturer & Supplier: TX Solar's High Quality Commercial Lighting

YANGZHOU, JIANGSU, CHINA, September 17, 2026 / EINPresswire.com/ -- Commercial real estate developers, logistics hub operators, and business campus managers require dependable outdoor illumination for perimeter corridors and parking plazas. Deploying conventional grid-connected lighting across expansive commercial sites involves substantial underground trenching, heavy cabling, and extended utility interconnection reviews. To bypass complex cabling constraints and accelerate commissioning schedules, Yangzhou Tianxiang Road Lamp Equipment Co., Ltd. manufactures engineered commercial lighting solutions. Known internationally as TX Solar, the company combines 2008 founding credentials with manufacturing heritage dating back to 1996. TX Solar operates a 62,000 square meter manufacturing base equipped with over 220 specialized production units. The factory produces advanced all-in-one solar street light systems that integrate solar modules, storage batteries, and smart luminaires. These self-contained commercial lighting units deliver stable off-grid illumination across diverse business and industrial properties worldwide.





Commercial facility managers and electrical engineering contractors evaluate high-performance integrated commercial luminaires from TX Solar across five primary technical dimensions:

Commercial Luminaire Scaling and Bat-Wing Optical Distribution: Configuring scalable wattage outputs from 10W to 150W with specialized bat-wing lenses for broad, uniform ground coverage.
Integrated Monocrystalline Generation and Aerodynamic Housing: Incorporating high-efficiency monocrystalline solar panels within a streamlined aluminum enclosure featuring an optional automatic self-cleaning wiper mechanism.
Thermal-Isolated Lithium Iron Phosphate Energy Storage: Sizing high-capacity lithium iron phosphate battery packs with internal thermal barriers to sustain stable electrochemical cycles across wide temperature ranges.
High-Speed MOSFET MPPT and Weather-Adaptive Control: Integrating an advanced MPPT controller with high-speed MOSFET pre-drive circuitry and microcomputer weather judgment algorithms for optimized power regulation.
Rapid Zero-Trenching Installation and Modular CCTV Expansion: Enabling swift single-technician mounting on standard poles or structural facades with optional high-definition wireless CCTV camera modules for enhanced facility security.

Commercial Luminaire Scaling and Bat-Wing Optical Distribution

Commercial properties demand tailored lighting outputs across distinct operational areas. Pedestrian pathways, office courtyard perimeters, and garden walkways require gentle, glare-controlled illumination between 10W and 30W. Busy internal transit routes, cargo loading docks, and industrial storage yards benefit from mid-range ratings between 40W and 80W. Broad commercial parking plazas and container freight depots deploy high-output configurations up to 150W for expansive nighttime visibility. For example, standard 100W commercial configurations pair a 160W monocrystalline panel with a 25.6V 48Ah lithium iron phosphate battery. To expand illuminated ground surface area and widen luminaire spacing, TX Solar incorporates precision bat-wing optical lenses. These specialized optical lenses disperse luminous flux across an expanded longitudinal angle of 140 degrees by 70 degrees. This beam distribution maintains uniform ground luminance while reducing the total number of poles required across commercial parking lots. The resulting optical layout lowers initial capital investment for commercial property owners and improves visual comfort for visitors.

Integrated Monocrystalline Generation and Aerodynamic Housing

The photovoltaic generation module sits flush across the upper chassis of the luminaire, removing exposed wires and external mounting brackets. TX Solar encapsulates high-efficiency monocrystalline silicon solar cells within dedicated in-house production workshops. Each solar module features low-iron tempered glass with high light transmittance to enhance daily energy absorption under overcast skies. The luminaire chassis combines heavy-duty profile aluminum with precision die-cast aluminum components to optimize structural rigidity and thermal dissipation. An aerodynamic geometric profile allows rainwater to drain naturally, helping wash away loose dust and environmental airborne debris. For dry industrial yards, cement facilities, or desert logistics parks, TX Solar provides an optional automatic self-cleaning wiper mechanism. This integrated motorized wiper sweeps across the solar panel face at programmed intervals without requiring manual facility labor. Automated surface maintenance helps preserve

photovoltaic intake and stabilizes ongoing charging performance across challenging commercial working environments.

Thermal-Isolated Lithium Iron Phosphate Energy Storage
Energy storage performance directly governs how reliably a commercial solar luminaire maintains continuous lighting throughout multi-day overcast periods. TX Solar equips its all-in-one series with dedicated lithium iron phosphate battery cells built inside specialized workshop facilities. Lithium iron phosphate chemistry provides exceptional thermal stability, deep discharge tolerance, and extended operational cycle life compared to traditional cells. Because all-in-one luminaires house the battery directly beneath the solar panel, thermal management within the compact enclosure is essential. TX Solar engineers incorporate dedicated thermal insulation barriers and heat sinks between the photovoltaic panel and the internal battery enclosure. This protective thermal barrier shields sensitive electrochemical components from solar heat absorption during peak daylight operation. Consequently, the integrated battery sustains steady charge acceptance across ambient temperatures from minus 20 to plus 65 degrees Celsius. High usable depth of discharge supports multiple nights of autonomy without requiring grid power or generator backup.

High-Speed MOSFET MPPT and Weather-Adaptive Control
The internal charge and lighting controller manages energy conversion between the photovoltaic panel, lithium battery, and LED light engine. TX Solar integrates a proprietary MPPT power supply controller engineered with a high-speed MOSFET pre-drive circuit architecture. This specialized gate drive topology accelerates switching frequency and shortens dynamic response times during fluctuating solar irradiance levels. Consequently, the controller improves photovoltaic charging efficiency and mitigates thermal dissipation losses across the power regulation stage. An embedded microcomputer control system incorporates intelligent power regulation algorithms paired with automated weather judgment capabilities. The controller analyzes real-time voltage patterns and daily charging rates to determine current meteorological conditions and available stored reserves. Based on these readings, the firmware executes reasonable discharge planning across distinct operating intervals throughout the night. Luminaires deliver full brightness during peak commercial operational hours and automatically transition to energy-conserving profiles during early morning periods. This smart regulation preserves battery reserves while supporting compliant commercial illuminance from dusk until dawn.

Rapid Zero-Trenching Installation and Modular CCTV Expansion
Upgrading commercial property lighting often encounters severe constraints from paved parking surfaces, landscaped lawns, and active warehouse roadways. Traditional illumination requires destructive asphalt trenching, conduit laying, electrical distribution panels, and complex municipal permitting procedures. TX Solar all-in-one luminaires remove external cabling requirements, allowing direct attachment to existing structural poles, building facades, or boundary walls. A single field technician can complete mechanical mounting and angle adjustment in 10 to 15 minutes per unit. Standardized universal mounting sleeves fit straight poles, tenons, and wall brackets with adjustable tilt angles for optimal solar exposure. For

security-sensitive corporate perimeters, logistics yards, and commercial business parks, TX Solar offers an optional integrated CCTV surveillance module. The high-definition camera module mounts directly into the luminaire chassis, powered continuously by the internal solar energy storage system. Wireless network transmission enables real-time facility video monitoring alongside reliable area lighting without adding separate wiring or mounting poles.

Commercial Procurement Value and Direct Factory Sourcing
Sourcing all-in-one commercial solar luminaires directly from an integrated source manufacturer provides measurable cost efficiencies and technical accountability. Factory-direct procurement removes intermediary distribution markups while assuring full mechanical and electrical compatibility across all internal sub-assemblies. TX Solar operates specialized in-house production workshops for photovoltaic encapsulation, lithium battery pack assembly, and aluminum luminaire die-casting. Supported by 63 technical patents and 16 engineering specialists, the technical department provides professional DIALux photometric calculations for commercial projects. Engineers deliver customized illuminance simulations, pole layout recommendations, and optical uniformity analyses tailored to specific facility dimensions. Quality control inspectors conduct multi-point functional inspections on every lighting assembly before overseas packing and export dispatch. TX Solar offers rapid 7-day turnaround for evaluation samples and maintains reliable 20 to 30 day bulk order manufacturing timelines. Having delivered over 1,700,000 luminaires across more than 20 countries, TX Solar provides scalable manufacturing capacity for global commercial tenders.
Commercial contractors and facility developers can examine detailed specifications for our integrated solar street lighting series on the official portal. Request customized DIALux commercial project simulations, sensor configuration data, and competitive factory-direct quotations at https://www.txzmlamp.com/.

Yangzhou Tianxiang Road Lamp Equipment Co., Ltd.
Yangzhou Tianxiang Road Lamp Equipment Co., Ltd.
+ +86 13905254640
email us here
Visit us on social media:
Facebook
YouTube
X

This press release can be viewed online at: https://www.einpresswire.com/article/942911110

EIN Presswire's priority is source transparency. We do not allow opaque clients, and our editors try to be careful about weeding out false and misleading content. As a user, if you see something we have missed, please do bring it to our attention. Your help is welcome. EIN Presswire, Everyone's Internet News Presswire™, tries to define some of the boundaries that are reasonable in today's world. Please see our Editorial Guidelines for more information.
© 1995-2026 Newsmatics Inc. All Right Reserved.