Single-Phase Pole-Mounted Transformers: Overhead Rural Electrification Solutions by XIAOWEI

NANTONG, JIANGSU, CHINA, October 29, 2026 /EINPresswire.com/ -- NANTONG, China: Expanding electrical infrastructure across dispersed rural territories in Canada and the United States requires dependable overhead distribution equipment designed for severe climatic exposure. Rural distribution feeders extend over hundreds of miles across agricultural plains, mountainous corridors, and forested terrain, exposing pole-top equipment to high wind shears, freezing precipitation, lightning surges, and wide temperature swings. Deploying a single-phase pole-mounted transformer for rural electrification manufactured by Jiangsu Xiaowei Electric Co., Ltd. (XIAOWEI) provides electrical cooperatives and regional utilities with equipment compliant with ANSI/IEEE and CSA standards, combining hermetic tank sealing, high-efficiency core metallurgy, and dual-voltage versatility for decentralized overhead networks.

CERTIFICATE OF COMPLIANCE

Certificate Number: UL-US-2245071-0
Report Reference: E528870-20221121
Date: 5-Dec-2022

Issued to: JIANGSU YAWEI TRANSFORMER CO. LTD
265 Huanghai Avenue West Hai'An, JIANGSU 226600
China

This is to certify that representative samples of: XPLH - Transformers, Distribution, Liquid-filled Type, Over 600 Volts

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: IEEE C57.12.00, 1st Ed., Issue Date: 2021-11-09, IEEE C57.12.28, 1st Ed., Issue Date: 2014-05-16

Additional Information: See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Deborah Jennings-Conner, VP Regulatory Services
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

Overhead Distribution Conditions and Remote Grid Challenges

Rural power grids operate under operating dynamics that differ significantly from underground urban topologies. Long distribution lines exhibit increased line impedance, fluctuating load profiles, and exposure to

environmental disturbances. Because pole-top units are mounted on wooden or concrete utility poles in remote locations, minimizing physical maintenance requirements and operational failure rates is central to utility planning. Overhead installations require mechanical tank integrity to resist corrosion, thermal endurance to handle peak agricultural irrigation or winter heating loads, and dielectric stability across sub-zero northern conditions.

Mechanical Tank Engineering and Severe Weather Enclosure Architecture

Pole-mounted transformers endure continuous exposure to atmospheric moisture, ultraviolet radiation, and mechanical vibration. XIAOWEI constructs single-phase pole-mounted units using heavy-gauge cold-rolled carbon steel or stainless steel tanks engineered in accordance with ANSI/IEEE C57.12.20 and CSA C2.1 standards. The tank structure incorporates a continuous circular seam-welded base and a recessed domed cover that sheds rainwater and melting ice. Multi-stage surface pretreatment followed by electrostatically applied polyester powder coating creates a protective finish that exceeds IEEE C57 corrosion resistance specifications, protecting metal substrates from coastal salt fog and agricultural chemical exposure.

Mounting provisions include upper and lower heavy-duty hanger brackets compliant with ANSI dimensions, enabling secure attachment to standard utility poles. Each unit features lifting lugs engineered with verified safety margins, grounded eyebolt terminals, and tin-plated copper alloy secondary spade or clamp connectors to resist galvanic oxidation when connected to aluminum or copper conductors. To manage pressure fluctuations caused by ambient heating and peak loading cycles, the tank integrates an automatic self-resealing pressure relief valve. This device vents excessive internal gas pressure while preventing atmospheric moisture or particulate contamination from entering the sealed fluid reservoir.

Dielectric Fluid Technology and Thermal Endurance in Extreme Climates

Dielectric liquid functions as the primary electrical barrier and cooling medium within pole-mounted transformers. XIAOWEI offers single-phase units filled with refined mineral oil compliant with IEC 60296 or biodegradable natural ester FR3 fluid. Refined mineral oil maintains low kinematic viscosity at temperatures dipping down to -40 deg C, supporting free thermosiphon convective circulation (ONAN) across Canadian winter conditions without sluggish flow or localized overheating within winding ducts.

In agricultural watersheds, forested reserves, and environmentally sensitive rural zones, natural ester FR3 fluid provides a high-fire-point alternative. Exhibiting a fire point above 300 deg C and complete environmental biodegradability, natural ester fluid reduces environmental liabilities in the event of tank damage. In addition, the molecular affinity of natural ester for water molecules extracts moisture from Kraft paper insulation, reducing solid insulation degradation and supporting continuous transformer service life under seasonal overloading.

Core Metallurgy, Copper Windings, and Regulatory Energy Efficiency

Excitation losses in rural distribution networks persist continuously throughout the operating year, representing a major component of utility technical losses. XIAOWEI addresses excitation dissipation by building pole-mounted transformer magnetic cores from high-permeability, grain-oriented cold-rolled silicon steel laminations. Precision wound-core or step-lap mitered geometries align the magnetic flux vectors with the crystalline steel strip, lowering hysteresis loss and magnetizing current. Consequently, core excitation losses comfortably exceed United States Department of Energy (DOE) standards and Canadian CSA C802 energy efficiency benchmarks.

The electrical windings utilize 100% high-conductivity electrolytic copper conductors. In standard rural ratings, such as 37.5kVA units operating at primary distribution voltages up to 19.92kV and stepping down to 120/240V split-phase secondary service, circular winding geometry provides balanced mechanical support against radial burst forces during downstream electrical faults. High-temperature thermally upgraded insulation paper separates winding layers, supporting operation at 65 deg C average winding rise while accommodating short-duration overload peaks during harvest seasons or severe cold snaps.

Surge Protection Coordination and Dual-Voltage Versatility

Because overhead conductors act as collection paths for atmospheric lightning strikes and line switching surges, pole-mounted units require coordinated overvoltage protection. XIAOWEI transformers include pre-drilled tank mounting brackets designed for direct attachment of metal-oxide distribution surge arresters. The high-voltage primary terminals utilize wet-process electrical porcelain bushings or polymeric outdoor insulators engineered with extended creepage distances to avoid surface flashover during freezing rain or heavy dust contamination.

To assist electric utilities undergoing progressive distribution voltage upgrades, XIAOWEI supplies optional dual-voltage primary winding configurations controlled via an external de-energized tap changer. This architecture enables grid operators to deploy units at existing voltage levels (such as 7.2kV) and transition directly to higher distribution voltages (such as 14.4kV or 19.92kV) without replacing physical pole-top equipment. Coordinated internal weak-link fuses and secondary circuit breakers provide complete overcurrent coordination.

Direct Factory Sourcing and Global Technical Procurement Portal

Sourcing overhead distribution equipment directly from an established manufacturing plant gives rural electric cooperatives and EPC contractors transparent access to verified material test reports, certified design drawings, and direct engineering collaboration. Direct factory procurement minimizes intermediary markups and supports full compliance with UL, CSA, ANSI, and IEC quality control mandates.

Backed by 20 years of specialized transformer manufacturing experience, XIAOWEI maintains

modern production facilities and systematic testing protocols to support rural electrification initiatives across North America and international markets. To obtain single-phase pole-mounted transformer technical data sheets, review CAD dimensional models, request type test documentation, or receive volume export quotations, visit the official company website: https://www.xiaoweipower.com. Experienced technical sales engineers remain available to assist utility planning teams with custom tapping arrangements, cold-weather specifications, and international distribution project logistics.

Jiangsu Xiaowei Electric Co., Ltd.
XIAOWEI
Visit us on social media:
Facebook

This press release can be viewed online at: https://www.einpresswire.com/article/953048276

EIN Presswire's priority is source transparency. We do not allow opaque clients, and our editors try to be careful about weeding out false and misleading content. As a user, if you see something we have missed, please do bring it to our attention. Your help is welcome. EIN Presswire, Everyone's Internet News Presswire™, tries to define some of the boundaries that are reasonable in today's world. Please see our Editorial Guidelines for more information.
© 1995-2026 Newsmatics Inc. All Right Reserved.